



HOT AIR LANCE



HAL

The Marathon Hot Air Lance is a high temperature, high velocity, hot air lance that will easily dry moisture from the pavement allowing the operator to crack seal much faster! This process is ideal for the preparation of crack sealing because it allows for superior adhesion of the crack sealant into the asphalt. This process extends the life of the repair for years to come!

FEATURES

Torch

- All stainless steel construction, air valve, propane valve, deflector assembly and adjustable shoulder strap.

Air Hose

- 3/4" x 40 ft hose with Chicago quick disconnect & compressor fittings. Hose is wrapped in protective cover to minimize damage.
- 3/8" 41' Propane hose comes equipped with vapour propane regulator & protective hose cover to minimize damage.

Propane Consumption

- 5.57 lbs/hr at 20 psi

Propane Supply

- 20 psi (use min 100 lb-vapour withdrawal tank)

SPECS

Compressed Air Consumption	80 CFM at 100 psi
Torch Length	47 1/2"
Torch Weight	11 lbs (5 kg)
Air Output Temperature	2500°F
BTU Rating	150,000 BTU/hr
Propane Supply	20 psi (use min 100 lbs - vapour withdrawal tank)
Propane Consumption	5.57 lbs/hr at 20 psi

OPTIONS



Wheel Kit

Our Marathon wheel kit is an excellent accessory to add to your Hot Air Lance. This kit provides easy maneuverability and helps to deflect flying debris.



Viper Gas Rotary Screw Air Compressor

Gas-Powered Transportability

The Viper air compressor provides mobile power when and where you need it, with the flexibility of a gas-powered rotary screw air compressor. The Viper offers heavy-duty power, on or off your truck bed and gives you the flexibility only a transportable unit can offer.