

UNDER FIRED HOT TACK KETTLES



KEB115PT

Available sizes: 115 gal | 260 gal | 500 gal

Marathon's under fired hot tack sprayers provide a fast and reliable means of heating and applying solvent based emulsions, tack coats and asphalt cement. Our units are capable of heating a large volume of material on a steady basis and offer many operator friendly features and options.

FEATURES

- Manufactured with 10 GA steel for a long service life.
- 1" Ceramic blanket insulation added to retain heat.
- Units come equipped with a large 18" x 26" reverse-load, anti-splash lid for operator safety.
- Electric brakes and breakaway kits come standard on all trailer mounted equipment.
- Low profile for safe and easy loading and towing.
- Diesel heating system (available on 260gal and 500gal models only)

SPECS

All "KEB" models maximum operating temperature is 320°F

Models	KEB115PT	KEB260PT	KEB500PT
Shipping Weight	1,315 lbs (596 kg)	2,839 lbs (1,288 kg)	3,589 lbs (1,627 kg)
Dimensions			
Overall Length	158"	192"	224"
Overall Width	54"	80″	90"
Overall Height	68"	70"	70"
Loading Height	52"	52"	52"
Material Capacity	115 gal (435 L)	260 gal (983 L)	500 gal (1,892 L)
Burner	(1) 410,000 BTU vapour propane	(1) 410,000 BTU vapour propane	(1) 410,000 BTU vapour propane
Suspension			
Axle(s)	Single	Single	Tandem
Capacity	3,500 lbs (1,591 kg)	5,200 lbs (2,363 kg)	10,400 lbs (4,718 kg)
Tires	(2) 205/75/R15	(2) 225/75/R15	(4) 225/75/R15

OPTIONS

- Power spray system with 5hp engine and flushing tank
- Digital automatic temperature control system (standard on diesel models)
- Diesel fired with automatic temperature control system (260 gal and 500 gal models only)
- 12 gallon recovery tank
- Hydraulic surge brakes
- Amber strobe light
- Flashing arrow stick with LED arrow ends
- Spare tire and rim mounted