

# **2 TON ASPHALT HOTBOX**



# HMT4000-ODL

Available size: 2 Tons / 4,000 lbs

Marathon's Premium Asphalt Hot Boxes are heavy duty, fully insulated, and customizable to suit your needs! Our units are diesel fired and equipped with an oil jacketed material vat to keep your asphalt warmer for longer periods of time when traveling between job sites. The hydraulic scissor hoist creates superior stability when unloading asphalt, to decrease operator fatigue & keep your crews working! These units are ideal for Cities and Municipalities, as well as contractors both big and small!

# **FEATURES**

- Material vat is polyhedral in construction, with a 10° rear-sloped floor, and all other walls channeling material directly towards rear gate.
- Single electric actuator top loading door opens 107° and covers front burner and components from spillage when loading at the asphalt plant.
- Tandem axle trailer design is versatile with a low center of gravity which gives the unit more stability.
- An 8 gallon tool rinse tank, 4 pc tool rack, 3 gallon release agent spray bottle with holder and 2 traffic cone holders come standard on all models.

## **SPECS**

Specifications HMT4000-ODL

Shipping Weight 4,000 lbs (1,814 kg)

Hot Mix Chamber 4,000 lbs (1,814 kg)

Overall Length 205"

Overall Width 81"

Overall Height 86"

Overall Height with Arrow Bar 102"

Overall Height with Door Up 125"

Hopper Opening (L x W) 52" L x 62" W Top Loading Door (L x W) 55" L x 70" W Rear Unloading Door (H x W) 11" H x 18" W

Capacity

Heat Transfer Oil 49 gal (185 L)

**Shoveling Platform** 

Height from ground 24"

Diesel Burner 165,000 BTU

Hopper Insulation 1" ceramic body

with 2" fiberglass lid

Suspension

Axle Tandem

Capacity 10,400lbs (4,716 kg) Tires (4) 225/75/R15

#### **OIL-JACKETED FEATURES**

Our equipment has a reputation for outlasting the competition! Oil jacketed units have a longer lifespan in comparison to air jacketed versions as the oil absorbs the heat generated by the burner and the flame no longer acts as the heat source for the asphalt, saving the lifespan of the steel.

Oil jacketed units produce even heat distribution throughout the whole hopper so that asphalt doesn't burn or soften unevenly throughout. Our design has superior heat retention and comes standard with automatic temperature control to consistently maintain the quality of your product and eliminate the need for frequent burner on/off control.

Oil jacketed models feature a 120V overnight heater to keep asphalt warm overnight to minimize heat up time the next day.

#### HYDRAULIC DUMP FEATURES

42° hydraulic dumping angle plus the 10° provided by the floor guarantees maximum material output. Dual safety lock-out bars will support vat at 20° for maintenance.

Hydraulic scissor hoist for superior stability when dumping asphalt.

Fully enclosed hydraulic powerpack with a single magnetic & detachable operator pendant to allow hopper control from desired location.

Alarm sounds whenever tilt system is operated downwards for operator safety.

### **OPTIONS**

- 300,000 BTU hand held vapor propane torch with 15' hose
- 30 Gallon Insulated tack tank (heated/non-heated)
- Compactor Plate with hoist & Electric Winch
- Tool box installed
- Hydraulic surge brakes
- Spare tire & rim mounted
- Amber strobe light
- 2-5/16" Ball Hitch