

MASTIC MIXERS WITH AUGER



MM AUGER

Available Sizes: 250 gal | 350 gal

Designed to mix heavier, thicker, and denser mastic materials, the Helix Auger System allows you to dispense mastic material easily at a consistent rate. This allows for wider repairs using a 4' drag box that is pulled behind the trailer.

FEATURES

- Oil-Jacketed auger keeps material hot while dispensing mastic and pulls material out of the melter, without clogging.
- Control the flow of mastic at an easy and consistent rate, dispensing material in a uniform width.
- Manufactured with minimum 10 GA steel, fully welded, and constructed of heavy duty 6" channel and gusseted in locations for safety and strength.
- Engineered efficient hot airflow means quicker heat up time and less consumption of fuel!
- A safe, low-loading height designed to reduce operator strain and improve efficiency during loading of material.
- Agitation & auger system both feature forward pushing and rear drawing ability, allowing greater blending of all mastic materials rather than lifting it from the bottom of the material vat as competitor units do.
- Easy access to burner, engine, fuel, and hydraulic reservoirs for maintenance purposes.
- Overnight heaters help maintain heat transfer oil temperature, keeping material warm and reducing daily heat-up time.
- Large tool heater allows easy insertion and removal of all mastic tools and boxes required for the job!

SPECS

Models	MM250ADT	MM350ADT	
Shipping Weight	6,415 lbs (2,910 kg)	7,650 lbs (3,440 kg)	
Dimensions			
Overall Length	224"	252"	
Overall Width	82"	82.25"	
Overall Height	88.75"	90"	
Loading Height	62"	64"	
Auger Discharge Height	24.25"	26.75"	
Capacity			
Material Vat	250 gal (945 L)	350 gal (1,324 L)	
Heat Transfer Oil	45 gal (170 L)	67 gal (253 L)	
Diesel Fuel Tank	30 gal (113 L)	30 gal (113 L)	
Hydraulic Oil Tank	12 gal (46 L)	12 gal (46 L)	
Engine	23hp liquid cooled electric start, Kohler diesel	23hp liquid cooled electric start, Kohler diesel	
Burner	(1) 340,000 BTU diesel burner	(1) 340,000 BTU diesel burner	
Suspension			
Axle(s)	Tandem	Tandem	
Capacity	10,400 lbs (4,717 kg)	14,000 lbs (6,350 kg)	
Tires -size	(4) 225/75/R15	(4) 235/85/R16	
*Specifications subject to ch	ange without notice.		

OPTIONS

- Hydraulic surge brakes
- 2-5/16" ball hitch
- Spare tire and rim mounted
- Amber strobe light
- Flashing arrowstick with LED arrow ends
- Various size application smoothers, scrapers and squeegees.
- 12 gallon mastic dispenser
- Adjustable drag box up to 4'
- Dimensions: 67"L x 85"W x 41"H

