

# DIESEL FIRED MASTIC MIXERS



Marathon



## MM250DT

Available Sizes: 250 gal | 350 gal

Marathon is the leading manufacturer in the industry for engineering the best Mastic Mixers! Designed to mix mastic and bridge joint materials, the heavy duty construction allows mixing of heavy material mixed with aggregates. We offer more sizes and choices than anyone in the industry!

### FEATURES

- Manufactured with minimum 10 GA steel, fully welded and constructed of heavy duty 6" channel and gusseted in locations for safety and strength.
- Engineered efficient hot airflow means quicker heat up time and less consumption of fuel!
- Agitator has forward and rear drawing ability which blends the mastic materials better due to the ability to move mastic, not just lifting it from the bottom of the material vat as competitive units do.
- Easy access to burner, engine, fuel and hydraulic reservoirs for maintenance purposes.
- Overnight heaters keep material warm and reduce daily start-up time.
- Lower loading height of materials decreases operator fatigue and makes it safe and easy for operators to load material into the tank without having to step up on trailer.
- Low center of gravity for superior rear visibility when towing.
- The heated delivery chute pivots from side to side (greater pouring radius) and chute keeps materials hot while flowing out of the unit for easy mastic applications.
- Controls are fully digital, accuracy to within 5°.
- Tool heater is generous enough to get larger application tools in and out.

VISIT [MARATHONEQUIPMENTINC.COM](http://MARATHONEQUIPMENTINC.COM) PHONE: 1-888-999-4041 EMAIL: [INFO@MARATHONEQUIPMENTINC.COM](mailto:INFO@MARATHONEQUIPMENTINC.COM)

# SPECS

Models	MM250DT	MM350DT
Shipping Weight	6,349 lbs (2,880 kg)	7,007 lbs (3,178 kg)
<b>Dimensions</b>		
Overall Length	208"	236"
Overall Width	80"	80"
Overall Height	77"	79"
Loading Height	60"	62"
Delivery Chute Height	24"	27"
<b>Capacity</b>		
Material Vat	250 gal (945 L)	350 gal (1,324 L)
Heat Transfer Oil	45 gal (170 L)	65 gal (246 L)
Diesel Fuel Tank	30 gal (113 L)	30 gal (113 L)
Hydraulic Oil Tank	12 gal (46 L)	12 gal (46 L)
<b>Engine</b>		
	23hp liquid cooled electric start, Kohler diesel	23hp liquid cooled electric start, Kohler diesel
<b>Burner</b>		
	(1) 340,000 BTU diesel burner	(1) 340,000 BTU diesel burner
<b>Suspension</b>		
Axle(s)	Tandem	Tandem
Capacity	10,400 lbs (4,717 kg)	14,000 lbs (6,350 kg)
Tires -size	(4) 225/75/R15	(4) 235/85/R16

**\*Specifications subject to change without notice.**

# OPTIONS

- Heated square shoveling platform
- 2-5/16" ball hitch
- Spare tire and rim mounted
- Amber strobe light
- Flashing arrowstick with LED arrow ends
- Various size application smoothers, scrapers and squeegees



**12 gal Mastic Applicator (MD12)**